

e-1.

INDUSTRIAL TRAINING DEPARTMENT
TENDER NOTICE

No:ITI/CKDY/1051/2025-B1

Dt:17-12-2025

Sealed tenders are invited for supplying the following items for Govt.ITI Chalakudy, Railway Station Road, Chalakudy.P.O, Thrissur, Pin-680307.The Items should be supplied at the store.

Sl No	Name of item	specifications	Quantity
1	Bar magnet	Magnetic material : Cast Alnico 2 ,Length (in mm) : 50, Width (in mm) : 10 ,Height (in mm): 5 Maximum working temperature (in deg. C) : 450 Type of finish : Painted	2
2	Contactor & auxiliary contacts 3 phase, 415 Volt, 25 Amp with 2 NO and 2 NC	Contactor 4 pole phase, 415 Volt, 25 Amp, coil voltage 415V auxiliary contacts (2 NO+2 NC)	4
3	Limit Switch Liver operated 2 A, 500v, 2-contacts	Limit Switch Rated Current in A : 10 Total travel 70 degree Housing Cast Aluminium with detachable cover Maximum frequency of operation (cycles/ hour): 600 Rated Voltage(V AC): 500 Recommended travel: 25 degree Contacts: 2 NC	4
4	Rotary Switch 16 A/440v	"Maximum No of Switching positions (In Nos) 4 No. of Phase:3 ,Rated frequency (in Hz): 50 Rated operational Voltage (in Volt): 415 Rated operational current (in A): 16	3
5	Insulators including hardware fitting	Pin Type insulators, including Hardware fitting,LT and HT – 1 set.	1
		Shackle type insulators, including Hardware fitting, LT and HT,(1 set)	1
		Egg type insulators, including Hardware fitting, LT and HT , (1 set)	1
		Suspension type insulators including Hardware fitting, LT and HT , (1 set)	1
6	Knife Switch DPDT fitted with fuse terminals 16 Amp	Knife Switch DPDT fitted with fuse terminals 16 amp	8

7	Knife Switch TPDT fitted with fuse terminals 16 amp /440 V	Knife Switch TPDT fitted with fuse terminals 16 amp/ 440 V	8
8	Earth Plate	A. Earth Plate Copper 60cm X 60cm X 3.15mm Copper Plate Conformity to Standards IS 3043 : 1987 Thickness of Plate:3.15 millimeter Length of Plate:600 millimeter Width of Plate:600 millimeter Surface area of Plate(Sq meter) 1.90-2.0 Weight of Plate:10 kilogram Shape: Square	1
		B. Earth Plate GI 0cm X 60cm X 6mm GI Plate Conformity to Standards IS 3043 : 1987 Thickness of Plate: 6.3 millimeter Length of Plate: 600 millimeter Width of Plate:600 millimeter Surface area of Plate (Sq.meter) 1.60- 1.65 shape: Square	1
9	Earth Electrode Primary Electrode 2100x28x3.25mm Secondary Cu Strip 20X5mm	Earth Electrode A. Primary Electrode Material: Galvanized Iron Diameter: 50 millimeter Length of Rod: 2 meter Thickness: 3 millimeter Class of pipe:B B. Cu Strip Size: 20x5mm, length 10 M	2
10	Rechargeable battery 12 V, 100 Ah	Rechargeable battery Marked IS: 15549/2005 Battery Voltage: 12 Volt Battery Capacity (in Ah) at 10 H Rate : 100 Ah Material of Container: Polypropylene Co- polymer (PPCP), Number of cells per battery: 6 Cells for 12 Volt , 4.5 of IS:15549:2005 latest: Glass Mat	4
11	Rechargeable battery 6 V, 7 Ah	Rechargeable battery Battery Type: Lead Acid Battery, Sealed Chargeable Type: Rechargeable Voltage rating: 6 V, capacity : 7 Ah	4
12	LED Lights 12 V DC, 5 W	Light Type LED, Wattage 5 Watts, Voltage 12 Volts, Colour Temperature:6500 Kelvin	4
13	LED Lights 6 V DC, 5 W	Light Type LED Wattage 5 Watts, Voltage 6 Volts Colour Temperature 6500 Kelvin.	4
		A. Solar panels 250Wp, 12V Application class as per Cl. 3 of IS/IEC 61730-1 : 2004 Class AA. Solar panels 250Wp, 12V Application class as per Cl. 3 of IS/IEC	

14	Solar panels	61730-1 : 2004 Class A PV Module rating (in Wp): 250 Efficiency for PV Modules: >14% BIS CRS as per IS:IS 14286 (for Crystalline Silicon Terrestrial Photovoltaic (PV) modules) Corrosion resistant frame structure shall be provided to hold the SPV module: Yes PV Modules Construction, Testing and Safety requirements as per IEC 61730 (Part 1) and (Part 2) latest PV Modules shall comply Salt Mist Corrosion testing as per IEC:61701/IS:61701 latest	2
	Solar panels	B. Solar panels 15 Wp, 12V class as per Cl. 3 of IS/IEC 61730-1 : 2004 B. Solar panels 15 Wp, 12V class as per Cl. 3 of IS/IEC 61730-1 : 2004 Class A, PV Module rating (in Wp): 15, Efficiency for PV Modules: >14% BIS CRS as per IS:IS 14286 (for Crystalline Silicon Terrestrial Photovoltaic (PV) modules) Corrosion resistant frame structure shall be provided to hold the SPV module: Yes PV Modules Construction, Testing and Safety requirements as per IEC 61730 (Part 1) and (Part 2) latest, PV Modules shall comply Salt Mist Corrosion testing as per IEC:61701/IS:61701 latest	2
15	Solar charge controller with manual switch (Day lighting)	Solar Charge Controller 12V 10 A Manual Amps Maximum VOC of the to be Connected = 22 Volts, Panel Maximum Power = 200 Wp = 22 Volts, Panel Maximum Power = 200 Wp Type: MMPT Standard Application: Home Lighting system, DC Application of Lead acid /SMF Battery Voltage of 12 V. / Lithium Ion 11.1 Volts /Lithium Ferro Phosphate 12.8 Volts	4
16	Motion Detector	Motion Detector input: 220 -240 V ac Mount Type: Wall Range: 12 m Time Delay: 8 s → 7 min	10
17	Lead Acid battery 75 Ah	Lead acid battery, 75 Ah, 12 V	2

The tender should be superscribed as "Govt. ITI Chalakudy Wireman trade Miscellaneous Items", Tender Number and addressed to the Principal,

Govt. ITI Chalakudy, Thrissur -680307. More details can be had from the office on all working days at prescribed office hours.

Tender Notice Number	: ITI/CKDY/1051/2025-B1
Cost of Tender Form	: 0.20 % of Tender amount (Rounded to the nearest multiples of 100 Minimum of ₹ 500/- & Max: 1500/-)
EMD	: 1 % of total cost
Last date of sale of tender form	: 12/01/2026 3 PM
Last date of receipt of tender	: 13/01/2026 3 PM
Date & time of opening of tender	: 13/01/2026 4 P M

Those who wish to get the tender forms by post should sent an extra amount of ₹100/- by way of money order. No other form of remittance will be accepted. On satisfactory acceptance of tender, it should be accompanied by an agreement in ₹200/- Kerala stamp paper and security deposit @5% of tender amount. Warranty/Guaranty of the items should be mentioned in tender. The rate of items should be valid till 20/03/2026. The tenders are not transferable.

Principal

Signed by Sindu Paul

Date: 17-12-2025 15:46:50

INDUSTRIAL TRAINING DEPARTMENT
TENDER NOTICE

No:ITI/CKDY/1091/2025-B1

Dt: 22-12-2025

Sealed tenders are invited for supplying the following items for Govt. ITI Chalakudy, Railway Station Road, Chalakudy.P.O, Thrissur, Pin-680307. The Items should be supplied at the store.

SI No	Name of items and specifications	Quantity
1	<u>Steel rule 300 m</u> Nominal Size (cm): 30 Type of Steel Scale (Graduation on both edges): BB Certification Steel Scale confirming to IS: 1481 Material :spring Steel	39
2	<u>Screw Driver 200 m</u> Length of Blade in mm :200 Insulation on Blade, Length of Handle in mm: 100 ,Tip Size (a x b) in mm x mm: 1.2 x 8.0 Shape of Blade: Round, high grade silicon manganese steel, magnitised tip, Conformity to Standards IS : 844 Part I and Part II latest	4
3	<u>Terminal screw Driver 75 mm (Connector)</u> Conformity to Standards IS : 844 Part 1 and Part II latest Medium Grip Screwdrivers Insulation on Blade Tip Size (a x b) in mm x mm 0.6 x 5 Shape of Blade: Round, high grade silicon 75 mm (Connector) manganese steel, magnitised tip Length of Blade in mm: 75	26
4	<u>Knife Double Bladed Electrician</u> Folding type: 100 mm length TWIN BLADES: One straight one curved Blade: Carbon steel Handle: Wooden, user friendly	38
5	<u>Plumb bob 115 grams</u> Body Material: Cast Iron, Weight:200 g Shape: Conical, Head: Wood / plastic	40
6	<u>Neon tester pencil bit type 500Volt</u> Conformity to Standards I.S.5579 -1985, Length of Handle : 100 millimeter Handle Material : Cellular Acetate Plastic , Length of Blade :100 millimeter Blade Plating: Nickel Chrome Material of Blade :Silicon-Manganese Steel Tip Thickness : 0.5 millimeter Maxmum Voltage for Testing (Direct Current) : 500 Volt	42

The tender should be superscribed as "Govt.ITI Chalakudy Wireman trade Trainees Tool Kit", Tender Number and addressed to the Principal, Govt.ITI Chalakudy, Thrissur -680307. More details can be had from the office on all working days at prescribed office hours.

Tender Notice Number	: ITI/CKDY/1091/2025-B1
Cost of Tender Form	: 0.20 % of Tender amount (Rounded to the nearest multiples of 100) (Minimum of ₹600/- & Max: 1,500/-)
EMD	: 1 % of total cost
Last date of sale of tender form	: 16/01/2026 - 4 P M
Last date of receipt of tender	: 17/01/2026 - 3 P M
Date & time of opening of tender	: 17/01/2026 - 4 P M

Those who wish to get the tender forms by post should sent an extra amount of ₹ 100/- by way of money order. No other form of remittance will be accepted. On satisfactory acceptance of tender, it should accompanied by an agreement in ₹200/-Kerala stamp paper and security deposit @ 5% of tender amount. Warranty/Guaranty of the items should be mentioned in tender. The rate of items should be valid till 25/03/2026. The tenders are not transferable.

Principal

Signed by Sindu Paul

Date: 22-12-2025 13:03:29

വ്യാവസായിക പരിശീലന വകുപ്പ്

ടെണ്ടർ നോട്ടീസ്

നമ്പർ : ITI/CKDY/1091/2025-B1

തീയതി: 22-12-2025

തൃശ്ശൂർ ജില്ലയിലെ, ചാലക്കുടി ഗവ. ഐ.ടി.ഐ യിലെ വയർമാൻ (Wireman) ട്രേഡിലേക്ക് താഴെ പറയുന്ന സാധനങ്ങൾ സംഭരണം ചെയ്യുന്നതിന് സീലുവച്ച ദർഘാസുകൾ ഷണിച്ച് കൊള്ളുന്നു. സാധനങ്ങൾ ചാലക്കുടി ഗവ. ഐ.ടി.ഐ സ്റ്റോറിൽ എത്തിക്കേണ്ടതാണ്.

ക്രമ നമ്പർ	സാധനങ്ങളുടെ പേര്, സ്പെസിഫിക്കേഷൻ	എണ്ണം
1	<u>Steel rule 300 m</u> Nominal Size (cm): 30 Type of Steel Scale (Graduation on both edges): BB Certification Steel Scale confirming to IS: 1481 Material :Spring Steel	38
2	<u>Screw Driver 200 m</u> Length of Blade in mm :200 Insulation on Blade, Length of Handle in mm: 100 ,Tip Size (a x b) in mm x mm: 1.2 x 8.0 Shape of Blade: Round, high grade silicon manganese steel, magnitised tip, Conformity to Standards IS : 844 Part I and Part II latest	4
3	<u>Terminal screw Driver 75 mm (Connector)</u> Conformity to Standards IS : 844 Part 1 and Part II latest Medium Grip Screwdrivers Insulation on Blade Tip Size (a x b) in mm x mm 0.6 x 5 Shape of Blade: Round, high grade silicon 75 mm (Connector) manganese steel, magnitised tip Length of Blade in mm: 75	26
4	<u>Knife Double Bladed Electrician</u> Folding type: 100 mm length TWIN BLADES: One straight one curved Blade: Carbon steel Handle: Wooden, user friendly	38
5	<u>Plumb bob 115 grams</u> Body Material: Cast Iron, Weight: 200 g Shape: Conical, Head: Wood /plastic	40
6	<u>Neon tester pencil bit type 500Volt</u> Conformity to Standards I.S.5579 -1985, Length of Handle : 100 millimeter Handle Material : Cellular Acetate Plastic , Length of Blade :100 millimeter Blade Plating: Nickel Chrome Material of Blade :Silicon-Manganese Steel Tip Thickness : 0.5 millimeter Maxmum Voltage for Testing (Direct Current) : 500 Volt	42
7	<u>Try square 200 mm</u> Blade material: Stainless Steel Length of Blade: 200 mm Width of Blade of in mm (with ± 2 mm tolerance) 30 Graduations	19

	marking should be provided on blade Stock: Cast Iron	
8	<u>D.E. metric Spanner</u> Set of 6 (from 6x7 to 16x17) (6x7, 8x9, 10x11, 12x13, 14x15, 16x17) Material: Chrome Vanadium Steel Head Style: Open End Finish Type: Powder Coated Should confirm IS 2028:2004	25
9	<u>Screw driver set (set of 5) 100- 300 mm</u> Conformity to Standards IS : 844 Part 1 and Part II latest Electrician screw driver insulated blade Size: (100,150,200,250,and 300 mm) set of 5 Nos Shape of Blade: Round, high grade silicon manganese steel, magnetised tip	26
10	<u>File half round 2nd cut</u> 250 mm with wooden handle Material: High carbon steel (IS 1931-2000)	40
11	<u>File round 2nd cut</u> 150 mm 2nd cut with wooden handle Material: High carbon steel (IS 1931-2000)	41
12	<u>Soldering iron with stand (60w/240v)</u> rubber griphandle IS 959 (Latest) Bitttype:Knife Bit tip temp: 350° C	41
13	<u>Neon tester 230 Volt</u> Conformity to Standards I.S.5579 -1985, Length of Handle : 100 millimeter, Handle Material : Cellular AcetatePlastic, Length of Blade :75 millimeter, Blade Plating: Nickel Chrome Material of Blade :Silicon-Manganese Steel Tip Thickness:1 millimeter Maxmum Voltage for Testing (Direct Current) : 500 Volt	42
14	<u>Steel measuring tape Pocket type</u> Case material: ABS Blade material: Stainless steel Size,(m): 5, Lock Button:YES Blade width,(inch): 1 Blade thickness,(mm): 2	42
15	<u>Bradawl 150 mm x 6mm</u> Square pointed, wooden handle, Blade:Alloysteel BIS 10375 - 1982	38
16	<u>Set of Rawal punch</u> Material: Carbon steel Shank Type: Hex Size: 8, 10 mm	42
17	<u>Wooden mallet</u> 1 kg. (75mm x 15mm) hard wood	42

ദർശനം നമ്പർ

: ITI/CKDY/1091/2025-B1

ദർശനം വില

: ടെണ്ടർ തുകയുടെ 0.20 %ത്തെ 100൯റെ

ഏറ്റവും അടുത്ത ഗുണിതത്തിലേക്ക്

നിജപെടുത്തിയ തുക (കറഞ്ഞത് -600

INDUSTRIAL TRAINING DEPARTMENT
TENDER NOTICE

No:ITI/CKDY/1167/2025-B1

Dt:18-12-2025

Sealed tenders are invited for supplying the following items for Govt. ITI Chalakudy, Railway Station Road, Chalakudy.P.O, Thrissur, Pin-680 307. The Items should be supplied at the store.

Sl No	Name of item	specifications	Quantity
1	Solar Traffic Light 12V, 75 Ah battery, 75 Wp solar panel, 12V, 10A dusk to dawn charge controller, 15 W LED lights with suitable colors and 9 m height pole all dismantable.	Solar Traffic Light , 12V, 75 Ah battery, 75 Wp solar panel, 12V, 10A dusk to dawn charge controller, 15 W LED lights (red yellow green) and 9 m height pole all dismantable. Traffic Light Controller sequencer Contains 39 + Sequences Red, Yellow, Green Light Delay Time is 0 – 250 s.	2
2	Solar street light lamp set 12 V, 18/24 watts.	Solar street light lamp set - power output of PV Module ≥ 24 Wp at 16.4 $\pm$ 0.2 Volt at STC Battery capacity ≥ 12.8 V (nominal) 75 Ah at STC Lithium Ferro Phosphate battery (LiFePo4) Type of LED (Light source): 24 Watt White LED type Ingress protection IP65 or better Nominal bore size of tube/Thickness of tube: 65 mm/3.6 mm Height of pole (in m:) 9 Battery box Battery included in the luminaire enclosure, with water proof (IP65 or better) and corrosion resistant PV Module Efficiency: $\geq 14\%$. The open circuit voltage of the PV modules under STC (in volts) :21, IEC 61215 edition II/IS 14286. BIS CRS compliance for PV Module as per IEC 61215 Edition II/Bis 14286 from NABL or IECQ accredited Laboratory Minimum warranty period for PV Modules (in Years)PV module warranted for output wattage $\geq 90\%$ at the end of 10 years and 80% at the end of 25 years. Total electronics efficiency : $\geq 90\%$	8

The tender should be superscribed as "Govt. ITI Chalakudy Wireman trade Solar Items", Tender Number and addressed to the Principal, Govt. ITI, Chalakudy, Thrissur -680 307. More details can be had from the office on all working days at prescribed office hours.

Tender Notice Number : ITI/CKDY/1167/2025-B1

Cost of Tender Form : 0.20 % of Tender amount (Rounded
to the nearest multiples of 100) (
Minimum of ₹ 900/- & Max: 1500/-)

EMD : 1 % of total cost

Last date of sale of tender form : 13/01/2026 4 PM

Last date of receipt of tender : 14/01/2026 3 PM

Date & time of opening of tender : 14/01/2026 4 P M

Those who wish to get the tender forms by post should sent an extra amount of ₹100/- by way of money order. No other form of remittance will be accepted. On satisfactory acceptance of tender, it should accompanied by an agreement in ₹200/-Kerala stamp paper and security deposit @ 5% of tender amount. Warranty/Guaranty of the items should be mentioned in tender.

The rate of items should be valid till 21/03/2026. The tenders are not transferable.

Principal

Signed by Sindu Paul
Date: 18-12-2025 17:17:45

ഗവ.ഐ.ടി.ഐ ചാലക്കുടി ചാലക്കുടി.പി.ഒ.

തൃശ്ശൂർ -680307 കേരളം:

ഇ-മെയിൽ : coe.itichalakudy@gmail.com

ITI/CKDY/1167/2025-B1

തീയതി: 18-12-2025

ദർഘാസ് പരസ്യം

ഈ സ്ഥാപനത്തിലെ വയർമാൻ ട്രേഡിലേക്ക് സോളാർ ഐറ്റംസ് വിതരണം നടത്താൻ താല്പര്യമുള്ള സ്ഥാപനങ്ങളിൽ നിന്നും മുദ്ര വച്ച ദർഘാസുകൾ ക്ഷണിച്ചുകൊള്ളുന്നു.

ക്രമ നമ്പർ	ടെണ്ടർ നമ്പരും ടെണ്ടർ തുറക്കുന്ന തീയതിയും അടങ്കൽ തുകയും	സാധന സാമഗ്രികൾ	ഒറിജിനൽ ഫാറത്തിന്റെ വില	പകർപ്പിന്റെ വില
1	2	3	4	5
1	ITI/CKDY/1167/2025-B1 @ 14/01/2026 ,4 P M Rs. 4,30,000/-	Solar Items	Rs.900/- + GST @ 18%	Rs.450/- + GST@18%

നിരത ദ്രവ്യം : ടെണ്ടർ തുകയുടെ 1 %

ടെണ്ടർ ഫോറം വിൽപ്പനക്ക്

ലഭിക്കുന്ന സ്ഥലം

: ഗവ.ഐ.ടി.ഐ ചാലക്കുടി,

ചാലക്കുടി.പി.ഒ, തൃശ്ശൂർ , 680 307, കേരളം.

മൊത്തം അടങ്കൽതുക

:4,30,000/-

പ്രിൻസിപ്പാൾ

Tender No: ITI/CKDY/1167/2025-B1 for the purchase of Solar Items in Wireman Trade at Govt ITI Chalakudy, Chalakudy PO, Thrissur.

Cost of original form of Tenders

: Rs. 900/- + GST @18%

Cost of duplicate form of tenders

: Rs. 450/- + GST @ 18%

Due date for the opening of tenders

: 14/01/2026, 04.00 p.m

Due date for the receipt of tenders

: 13/01/2026, 03.00 p.m

Date up to which the rates are to be remained same : 21.03.2026

Name and designation of the officer to whom the
The tenders are to be submitted

: Smt. Sindupaul, Principal,
Govt. ITI, Chalakudy.

Name of Office

: Government ITI, Chalakudy,
Thrissur.

Name of Items

: Solar items

Principal

Signed by Sindu Paul

Date: 18-12-2025 17:20:57

വ്യാവസായിക പരിശീലന വകുപ്പ്
ടെണ്ടർ നോട്ടീസ്

നമ്പർ : ITI/CKDY/1051/2025-B1

തീയതി: 17-12-2025

തൃശ്ശൂർ ജില്ലയിലെ, ചാലക്കുടി ഗവ. ഐ.ടി.ഐ യിലെ വയർമാൻ (Wireman) ട്രേഡിലേക്ക് താഴെ പറയുന്ന സാധനങ്ങൾ സംഭരണം ചെയ്യുന്നതിന് സീലുവച്ച ദർഘാസുകൾ ഷണിച്ച് കൊള്ളുന്നു. സാധനങ്ങൾ ചാലക്കുടി ഗവ. ഐ.ടി.ഐ സ്റ്റോറിൽ എത്തിക്കേണ്ടതാണ്.

ക്രമ നമ്പർ	സാധനങ്ങളുടെ പേര്	സ്പെസിഫിക്കേഷൻ	എണ്ണം
1	Bar magnet	Magnetic material : Cast Alnico 2 ,Length (in mm) : 50, Width (in mm) : 10 ,Height (in mm): 5 Maximum working temperature (in deg. C) : 450 Type of finish : Painted	2
2	Contactor & auxiliary contacts 3 phase, 415 Volt, 25 Amp with 2 No and 2 NC	Contactor 4 pole phase, 415 Volt, 25 Amp, coil voltage 415V auxiliary contacts (2 NO+2 NC)	4
3	Limit Switch Liver operated 2 A, 500v, 2-contacts	Limit Switch Rated Current in A : 10 Total travel 70 degree Housing Cast Aluminium with detachable cover Maximum frequency of operation (cycles/ hour): 600 Rated Voltage(V AC): 500 Recommended travel: 25 degree Contacts: 2 NC	4
4	Rotary Switch 16 A/440v	"Maximum No of Switching positions (In Nos) 4 No. of Phase:3 ,Rated frequency (in Hz): 50 Rated operational Voltage (in Volt): 415 Rated operational current (in A): 16	3
		Pin Type insulators, including Hardware fitting,LT and HT – 1 set.	1
		Shackle type insulators, including Hardware fitting, LT	1

5	Insulators including hardware fitting	and HT,(1 set)	
		Egg type insulators, including Hardware fitting, LT and HT , (1 set)	1
		Suspension type insulators including Hardware fitting, LT and HT , (1 set)	1
6	Knife Switch DPDT fitted with fuse terminals 16 Amp	Knife Switch DPDT fitted with fuse terminals 16 amp	8
7	Knife Switch TPDT fitted with fuse terminals 16 amp /440 V	Knife Switch TPDT fitted with fuse terminals 16 amp/ 440 V	8
8	Earth Plate	A. Earth Plate Copper 60cm X 60cm X 3.15mm Copper Plate Conformity to Standards IS 3043 : 1987 Thickness of Plate:3.15 millimeter Length of Plate:600 millimeter Width of Plate:600 millimeter Surface area of Plate(Sq meter) 1.90-2.0 Weight of Plate:10 kilogram Shape: Square	1
		B. Earth Plate GI 0cm X 60cm X 6mm GI Plate Conformity to Standards IS 3043 : 1987 Thickness of Plate: 6.3 millimeter Length of Plate: 600 millimeter Width of Plate:600 millimeter Surface area of Plate (Sq.meter) 1.60- 1.65 shape: Square	1
9	Earth Electrode Primary Electrode 2100x28x3.25mm Secondary Cu Strip 20X5mm	Earth Electrode A. Primary Electrode Material: Galvanized Iron Diameter: 50 millimeter Length of Rod: 2 meter Thickness: 3 millimeter Class of	2

		pipe:B B. Cu Strip Size: 20x5mm, length 10 M	
10	Rechargeable battery 12 V, 100 Ah	Rechargeable battery Marked IS: 15549/2005 Battery Voltage: 12 Volt Battery Capacity (in Ah) at 10 H Rate : 100 Ah Material of Container: Polypropylene Co- polyme (PPCP), Number of cells per battery: 6 Cells for 12 Volt , 4.5 of IS:15549:2005 latest: Glass Mat	4
11	Rechargeable battery 6 V, 7 Ah	Rechargeable battery Battery Type: Lead Acid Battery, Sealed Chargeable Type: Rechargeable Voltage rating: 6 V, capacity : 7 Ah	4
12	LED Lights 12 V DC, 5 W	Light Type LED, Wattage 5 Watts, Voltage 12 Volts, Colour Temperature: 6500 Kelvin	4
13	LED Lights 6 V DC, 5 W	Light Type LED Wattage 5 Watts, Voltage 6 Volts Colour Temperature 6500 Kelvin.	4
		A. Solar panels 250Wp, 12V Application class as per Cl. 3 of IS/IEC 61730-1 : 2004 Class AA. Solar panels 250Wp, 12V Application class as per Cl. 3 of IS/IEC 61730-1 : 2004 Class A PV Module rating (in Wp): 250 Efficiency for PV Modules: >14% BIS CRS as per IS:IS 14286 (for Crystalline Silicon Terrestrial Photovoltaic (PV) modules) Corrosion resistant frame structure shall be provided to hold the SPV module: Yes PV Modules Construction, Testing and Safety requirements as per IEC 61730 (Part 1) and (Part 2) latest PV Modules shall comply Salt Mist Corrosion testing as per IEC:61701/IS:61701	2

14	Solar panels	latest B. Solar panels 15 Wp, 12Vclass as per Cl. 3 of IS/IEC 61730-1 : 2004B. Solar panels 15 Wp, 12Vclass as per Cl. 3 of IS/IEC 61730-1 : 2004 Class A, PV Module rating (in Wp): 15, Efficiency for PV Modules: >14% BIS CRS as per IS:IS 14286 (for Crystalline Silicon Terrestrial Photovoltaic (PV) modules) Corrosion resistant frame structure shall be provided to hold the SPV module: Yes PV Moduels Constrution, Testing and Safety requirements as per IEC 61730 (Part 1) and (Part 2) latest,PV Modules shall comply Salt Mist Corrosion testing as per IEC:61701/IS:61701 latest	2
15	Solar charge controller with manual switch (Day lighting)	Solar Charge Controller 12V 10 A Manual Amps Maximum VOC of the to be Connected =22 Volts, Panel Maximum Power = 200 Wp =22 Volts, Panel Maximum Power = 200 Wp Type: MMPT Standard Application: Home Lighting system, DC Application of Lead acid /SMF Battery Voltage of 12 V. / Lithium Ion 11.1 Volts /Lithium Ferro Phosphate 12.8 Volts	4
16	Motion Detector	Motion Detector nput: 220 -240 V ac Mount Type: Wall Range: 12 m Time Delay: 8 s → 7 min	10
17	Lead Acid battery 75 Ah	Lead acid battery,75 Ah, 12 V	2

ദർഘാസ് നമ്പർ

: ITI/CKDY/1051/2025-B1

ദർഘാസ് വില

: ടെണ്ടർ തുകയുടെ 0.20 %ത്തെ 100൯റെ

ഏറ്റവും അടുത്ത ഗുണിതത്തിലേക്ക്

നിജപെടുത്തിയ തുക (കറഞ്ഞത് -500

രൂപ ,പരമാവധി -1,500 രൂപ) +ജി.എസ്.ടി(18%)

നിരത ദ്രവ്യം

: മൊത്ത വിലയുടെ 1 % ടെണ്ടറിന്റെ കൂടെ

വക്കേണ്ടതാണ്.

ദർഘാസ് വിലപ്പനയുടെ അവസാന തീയതി സമയം : 12. 01. 2026 3PM

മുദ്രവച്ച ദർഘാസുകൾ സ്വീകരിക്കുന്ന

അവസാനതീയതി, സമയം

: 13.01.2026 -3 PM

ദർഘാസുകൾ തുറക്കുന്ന തീയതി, സമയം

: 13.01.2026 - 4 PM

സ്ഥലം

: ഗവ.ഐ ടി, ചാലക്കുടി

ദർഘാസ് വില പണമായോ, മണി ഓർഡർ മുഖേനയോ മാത്രമേ സ്വീകരിക്കുകയുള്ളൂ. തപാലിൽ ലഭിക്കേണ്ടവർ 100/- (നൂറ്) രൂപ മാത്രം ദർഘാസ് വിലക്ക് പുറമേ അയക്കേണ്ടതാണ്. 200/- രൂപയുടെ കേരള സ്റ്റാമ്പ് പേപ്പറിൽ തയ്യാറാക്കിയ പ്രാഥമിക കരാർ പത്രം, ടെൻഡർ തുകയുടെ 5% സെക്യൂരിറ്റി ഡെപ്പോസിറ്റ് എന്നിവ ടെൻഡർ അംഗീകരിക്കുന്ന മുറയ്ക്ക് സമർപ്പിക്കേണ്ടതാണ്. ഇനങ്ങളുടെ വാറന്റി /ഗ്യാരന്റി സംബന്ധിച്ച് ടെൻഡറിൽ സൂചിപ്പിക്കേണ്ടതാണ്. ദർഘാസിൽ കാണിച്ചിരിക്കുന്ന തുകക്ക് 20/03/2026 തീയതി വരെ പ്രാബല്യം ഉണ്ടായിരിക്കേണ്ടതാണ്. ദർഘാസ് പ്രമാണം കൈ മാറാൻ പാടില്ല . ദർഘാസ് നമ്പർ, തീയതി എന്നിവ രേഖപ്പെടുത്തിയ മുദ്ര വച്ച കവറുകൾ പ്രിൻസിപ്പാൾ, ഗവ. ഐ.ടി.ഐ ചാലക്കുടി ,ചാലക്കുടി പി ഒ, തൃശ്ശൂർ 680 307 എന്ന വിലാസത്തിൽ ലഭിക്കേണ്ടതാണ്

പ്രിൻസിപ്പാൾ

Signed by Sindu Paul

Date: 17-12-2025 15:51:23

ഗവ.ഐ.ടി.ഐ ചാലക്കുടി
ചാലക്കുടി.പി.ഒ, തൃശ്ശൂർ -680 307

കേരള;

ഇ-മെയിൽ : coe.itichalakudy@gmail.com

ITI/CKDY/1051/2025-B1

തീയതി: 17-12-2025

ദർഘാസ് പരസ്യം

ഈ സ്ഥാപനത്തിലെ വയർമാൻ ട്രേഡിലേക്ക് മിസ്സപ്ലേനിയസ് ഐറ്റംസ് വിതരണം നടത്താൻ താല്പര്യമുള്ള സ്ഥാപനങ്ങളിൽ നിന്നും മുദ്ര വച്ച ദർഘാസുകൾ ക്ഷണിച്ചുകൊള്ളുന്നു.

ക്രമ നമ്പർ	ടെണ്ടർ നമ്പരും ടെണ്ടർ തുറക്കുന്ന തീയതിയും അടങ്കൽ തുകയും	സാധന സാമഗ്രികൾ	ഒറിജിനൽ ഫാറത്തിന്റെ വില	പകർപ്പിന്റെ വില
1	2	3	4	5
1	ITI/CKDY/1051/2025-B1 @ 13/01/2026 ,4 P M Rs. 2,40,250/-	Miscellaneous Items	Rs.500/- + GST @ 18%	Rs.250/- + GST@18%

നിരത ദ്രവ്യം : Rs.2,403/- (ടെണ്ടർ തുകയുടെ 1 %)

ടെണ്ടർ ഫോറം വിൽപ്പനക്ക് ലഭിക്കുന്ന സ്ഥലം

: ഗവ. ഐ.ടി.ഐ, ചാലക്കുടി,
ചാലക്കുടി.പി.ഒ, തൃശ്ശൂർ, 680 307, കേരള.

മൊത്തം അടങ്കൽതുക : 2,40,250/-

പ്രിൻസിപ്പാൾ

Tender No: ITI/CKDY/1051/2025-B1 for the purchase of Miscellaneous Items in Wireman Trade at Govt ITI Chalakudy, Chalakudy PO, Thrissur-680 307.

Cost of original form of Tenders : Rs. 500/- + GST @18%

Cost of duplicate form of tenders : Rs. 250/- + GST @ 18%
Due date for the opening of tenders : 13/01/2026, 04.00 p.m
Due date for the receipt of tenders : 13/01/2026, 03.00 p.m
Date up to which the rates are to be remained same : 20.03.2026

Name and designation of the officer to whom the
The tenders are to be submitted

: Smt. Sindupaul, Principal,
Govt. ITI, Chalakudy

Name of Office

: Government ITI, Chalakudy,
Thrissur.

Name of Items

: Miscellaneous items

Principal

Signed by Sindu Paul

Date: 17-12-2025 15:53:30

ഗവ.ഐ.ടി.ഐ ചാലക്കുടി
ചാലക്കുടി.പി.ഒ, തൃശ്ശൂർ -680307

കേരള;

ഇ-മെയിൽ : coe.itichalakudy@gmail.com

ITI/CKDY/1091/2025-B1

തീയതി: 22-12-2025

ദർഘാസ് പരസ്യം

ഈ സ്ഥാപനത്തിലെ വയർമാൻ ട്രേഡിലേക്ക് Trainees Tool Kit വിതരണം നടത്താൻ താല്പര്യമുള്ള സ്ഥാപനങ്ങളിൽ നിന്നും മുദ്ര വച്ച ദർഘാസുകൾ ക്ഷണിച്ചുകൊള്ളുന്നു.

ക്രമ നമ്പർ	ട്രേഡർ നമ്പരും ട്രേഡർ തുറക്കുന്ന തീയതിയും അടങ്കൽ തുകയും	സാധന സാമഗ്രികൾ	ഒറിജിനൽ ഫാറത്തിന്റെ വില	പകർപ്പിന്റെ വില
1	2	3	4	5
1	ITI/CKDY/1091/2025-B1 @ 17/01/2026 ,4 P M Rs. 2,96,510/-	Trainees Tool Kit	Rs.600/- + GST @ 18%	Rs.300/- + GST@18%

നിരത ദ്രവ്യം

: Rs.3000/-

ട്രേഡർ ഫോറം വിൽപ്പനക്ക്

ലഭിക്കുന്ന സ്ഥലം

: ഗവ.ഐ.ടി.ഐ ചാലക്കുടി,

ചാലക്കുടി.പി.ഒ, തൃശ്ശൂർ, 680 307,

കേരള.

മൊത്തം അടങ്കൽതുക

: 2,96,510/-

പ്രിൻസിപ്പാൾ

Tender No: ITI/CKDY/1091/2025-B1 for the purchase of Trainees Tool Kit in Wireman Trade at Govt ITI Chalakudy, Chalakudy PO, Thrissur.

Cost of original form of Tenders : Rs. 600/- + GST @18%
Cost of duplicate form of tenders : Rs. 300/- + GST @ 18%
Due date for the opening of tenders : 17/01/2026, 04.00 p.m
Due date for the receipt of tenders : 17/01/2026, 03.00 p.m
Date up to which the rates are to be remained same : 25.03.2026

Name and designation of the officer to whom the
The tenders are to be submitted : Smt. Sindupaul, Principal,
Govt. ITI, Chalakudy-680 307.

Name of Office : Government ITI Chalakudy,
Thrissur.

Name of Items : Trainees Tool Kit

Principal

Signed by Sindu Paul

Date: 22-12-2025 13:06:59

(രൂപ, പരമാവധി -1,500 രൂപ) +ജി.എസ്.ടി

നിരത ദ്രവ്യം

: മൊത്ത വിലയുടെ 1 % ടെണ്ടറിൻറെ കൂടെ

വക്കേണ്ടതാണ്.

ദർഘാസ് വിലപ്പനയുടെ അവസാന തീയതി സമയം :16. 01. 2026, 4 PM

മുദ്രവച്ച ദർഘാസുകൾ സ്വീകരിക്കുന്ന

അവസാന തീയതി, സമയം

: 17.01. 2026 - 3 P M

ദർഘാസുകൾ തുറക്കുന്ന തീയതി, സമയം

: 17.01. 2026 - 4 PM

സ്ഥലം

: ഗവ.ഐ ടി, ചാലക്കുടി

ദർഘാസ് വില പണമായോ, മണി ഓർഡർ മുഖേനയോ മാത്രമേ സ്വീകരിക്കുകയുള്ളൂ. തപാലിൽ ലഭിക്കേണ്ടവർ 100/- (നൂറ്) രൂപ മാത്രം ദർഘാസ് വിലക്ക് പുറമേ അയക്കേണ്ടതാണ്. 200/- രൂപയുടെ കേരള സ്റ്റാമ്പ് പേപ്പറിൽ തയ്യാറാക്കിയ പ്രാഥമിക കരാർ പത്രം, ടെണ്ടർ തുകയുടെ 5 % സെക്യൂരിറ്റി ഡെപ്പോസിറ്റ് എന്നിവ ടെണ്ടർ അംഗീകരിക്കുന്ന മുറയ്ക്ക് സമർപ്പിക്കേണ്ടതാണ്. ഇനങ്ങളുടെ വാറന്റി/ഗ്വാരണ്ടി സംബന്ധിച്ച് ടെണ്ടറിൽ സൂചിപ്പിക്കേണ്ടതാണ്. ദർഘാസിൽ കാണിച്ചിരിക്കുന്ന തുകക്ക് 25/03/2026 തീയതി വരെ പ്രാബല്യം ഉണ്ടായിരിക്കേണ്ടതാണ്. ദർഘാസ് പ്രമാണം കൈമാറാൻ പാടില്ല . ദർഘാസ് നമ്പർ, തീയതി എന്നിവ രേഖപ്പെടുത്തിയ മുദ്ര വച്ച കവറുകൾ പ്രിൻസിപ്പാൾ, ഗവ. ഐ.ടി.ഐ ചാലക്കുടി ,ചാലക്കുടി പി ഒ, തൃശ്ശൂർ 680 307 എന്ന വിലാസത്തിൽ ലഭിക്കേണ്ടതാണ്

പ്രിൻസിപ്പാൾ

Signed by Sindu Paul

Date: 22-12-2025 13:04:52

വ്യാവസായിക പരിശീലന വകുപ്പ്
ടെണ്ടർ നോട്ടീസ്

നമ്പർ : ITI/CKDY/1167/2025-B1

തീയതി: 18-12-2025

തൃശ്ശൂർ ജില്ലയിലെ, ചാലക്കുടി ഗവ. ഐ.ടി.ഐ യിലെ വയർമാൻ (Wireman) ടേഡിലേക്ക് താഴെ പറയുന്ന സാധനങ്ങൾ സംഭരണം ചെയ്യുന്നതിന് സീലുവച്ച ദർഘാസുകൾ ഷണിച്ച് കൊള്ളുന്നു. സാധനങ്ങൾ ചാലക്കുടി ഗവ. ഐ.ടി.ഐ സ്റ്റോറിൽ എത്തിക്കേണ്ടതാണ്.

ക്രമ നമ്പർ	സാധനങ്ങളുടെ പേര്	സ്പെസിഫിക്കേഷൻ	എണ്ണം
1	Solar Traffic Light 12V, 75 Ah battery, 75 Wp solar panel, 12V, 10A dusk to dawn charge controller, 15 W LED lights with suitable colors and 9 m height pole all dismountable.	Solar Traffic Light , 12V, 75 Ah battery, 75 Wp solar panel, 12V, 10A dusk to dawn charge controller, 15 W LED lights (red yellow green) and 9 m height pole all dismountable. Traffic Light Controller sequencer Contains 39 + Sequences Red, Yellow, Green Light Delay Time is 0 – 250 s.	2
2	Solar street light lamp set 12 V, 18/24 watts.	Solar street light lamp set - power output of PV Module ≥ 24 Wp at 16.4 $\pm$ 0.2 Volt at STC Battery capacity ≥ 12.8 V (nominal) 75 Ah at STC Lithium Ferro Phosphate battery (LiFePo4) Type of LED (Light source): 24 Watt White LED type Ingress protection IP65 or better Nominal bore size of tube/Thickness of tube: 65 mm/3.6 mm Height of pole (in m:) 9 Battery box Battery included in the luminaire enclosure, with water proof (IP65 or better) and corrosion resistant PV Module Efficiency: $\geq 14\%$. The open circuit voltage of the PV modules under STC (in volts) :21, IEC 61215 edition II/IS 14286. BIS CRS compliance for PV Module as per IEC 61215 Edition II/Bis 14286 from NABL or IECQ accredited Laboratory Minimum warranty period for PV Modules (in Years)PV module warranted for output wattage $\geq 90\%$ at the end of 10 years and 80% at the end of 25 years. Total electronics efficiency : $\geq 90\%$	8

ദർഘാസ് നമ്പർ

: ITI/CKDY/1167/2025-B1

ദർഘാസ് വില

: ടെണ്ടർ തുകയുടെ 0.20 %ത്തെ 100ൻറെ

ഏറ്റവും അടുത്ത ഗുണിതത്തിലേക്ക്

നിജപ്പെടുത്തിയ തുക (കുറഞ്ഞത് -900

രൂപ ,പരമാവധി -1,500 രൂപ) +ജി.എസ്.ടി

നിരത ദ്രവ്യം

: മൊത്ത വിലയുടെ 1 % ടെണ്ടറിൻറെ

കൂടെ വക്കേണ്ടതാണ്.

ദർഘാസ് വിലപ്പനയുടെ അവസാന

തിയതി, സമയം

:13. 01. 2026 - 4 PM

മുദ്രവച്ച ദർഘാസുകൾ സ്വീകരിക്കുന്ന

അവസാന തീയതി, സമയം

: 14. 01. 2026 - 3 PM

ദർഘാസുകൾ തുറക്കുന്ന തീയതി, സമയം

: 14.01.2026 - 4 PM

സ്ഥലം

: ഗവ.ഐ ടി, ചാലക്കുടി

ദർഘാസ് വില പണമായോ, മണി ഓർഡർ മുഖേനയോ മാത്രമേ സ്വീകരിക്കുകയുള്ളൂ. തപാലിൽ ലഭിക്കേണ്ടവർ 100/- (നൂറ്) രൂപ മാത്രം ദർഘാസ് വിലക്ക് പുറമേ അയക്കേണ്ടതാണ്. 200/- രൂപയുടെ കേരള സ്റ്റാമ്പ് പേപ്പറിൽ തയ്യാറാക്കിയ പ്രാഥമിക കരാർ പത്രം, ടെണ്ടർ തുകയുടെ 5 % സെക്യൂരിറ്റി ഡെപ്പോസിറ്റ് എന്നിവ ടെണ്ടർ അംഗീകരിക്കുന്ന മുറയ്ക്ക് സമർപ്പിക്കേണ്ടതാണ്. ഇനങ്ങളുടെ വാറന്റി /ഗ്യാരണ്ടി സംബന്ധിച്ച് ടെണ്ടറിൽ സൂചിപ്പിക്കേണ്ടതാണ്. ദർഘാസിൽ കാണിച്ചിരിക്കുന്ന തുകക്ക് 21/03/2026 തീയതി വരെ പ്രാബല്യം ഉണ്ടായിരിക്കേണ്ടതാണ്. ദർഘാസ് പ്രമാണം കൈ മാറാൻ പാടില്ല . ദർഘാസ് നമ്പർ, തീയതി എന്നിവ രേഖപ്പെടുത്തിയ മുദ്ര വച്ച കവറുകൾ പ്രിൻസിപ്പാൾ, ഗവ. ഐ.ടി.ഐ ചാലക്കുടി ,ചാലക്കുടി പി ഒ, തൃശ്ശൂർ 680 307 എന്ന വിലാസത്തിൽ ലഭിക്കേണ്ടതാണ്.

പ്രിൻസിപ്പാൾ

Signed by Sindu Paul

Date: 18-12-2025 17:19:20